

ESPECIFICAÇÕES GERAIS 2R1

VOLTAGEM	KVA NOMINAL A UPS	MODELO	CORRENTE NOMINAL	CHAVE NOMINAL*	DIM. RECINTO AL X AN X PRO PULG. (MM)	PESO LBS (KG)	INTERRUP .NOM. OPCION**
120 VAC, 1-fásico	3	1RBPED25M-12	25	55A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	40A
120 VAC, 1-fásico	5	1RBPED50M-12	42	55A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	60A
120 VAC, 1-fásico	7,5	1RBPED75M-12	63	95A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	80A
120 VAC, 1-fásico	10	1RBPED100M-12	83	95A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	125A
120 VAC, 1-fásico	15	1RBPED150M-12	125	175A	28 x 24 x 15.5 (711 x 609 x 394)	100 (45)	175A
120 VAC, 1-fásico	20	1RBPED200M-12	167	175A	28 x 24 x 15.5 (711 x 609 x 394)	100 (45)	225A
120 VAC, 1-fásico	30	1RBPED300M-12	250	280A	34 x 32 x 17 (863 x 812 x 431)	150 (68)	350A
120 VAC, 1-fásico	40	1RBPED400M-12	333	384A	34 x 32 x 17 (863 x 812 x 431)	150 (68)	450A
120 VAC, 1-fásico	50	1RBPED500M-12	417	576A	34 x 32 x 17 (863 x 812 x 431)	160 (73)	600A
120 VAC, 1-fásico	60	1RBPED600M-12	500	576A	34 x 32 x 17 (863 x 812 x 431)	175 (79)	Consulte a fábrica
120 VAC, 1-fásico	75	Consulte a fábrica	625	Solicite esta informação diretamente na fabrica da Delta.			
120 VAC, 1-fásico	100	Consulte a fábrica	833				
120/240, fase dividida	3	2RBPED30M	13	55A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	20A
120/240, fase dividida	5	2RBPED50M	21	55A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	30A
120/240, fase dividida	7,5	2RBPED75M	31	55A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	40A
120/240, fase dividida	10	2RBPED100M	42	55A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	60A
120/240, fase dividida	15	2RBPED150M	63	95A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	80A
120/240, fase dividida	20	2RBPED200M	83	95A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	125A
120/240, fase dividida	30	2RBPED300M	125	175A	28 x 24 x 15.5 (711 x 609 x 393)	125 (57)	175A
120/240, fase dividida	40	2RBPED400M	167	175A	28 x 24 x 15.5 (711 x 609 x 393)	125 (57)	225A
120/240, fase dividida	50	2RBPED500M	208	240A	34 x 32 x 17 (864 x 813 x 432)	150 (68)	350A
120/240, fase dividida	60	2RBPED600M	250	384A	34 x 32 x 17 (863 x 812 x 431)	175 (79)	Consulte a fábrica
120/240, fase dividida	75	2RBPED700M	313	384A	34 x 32 x 17 (863 x 812 x 431)	175 (79)	Consulte a fábrica
120/240, fase dividida	100	Solicite esta informação diretamente na fabrica da Delta.					
220, monofásico	3	RBPED30M-20	14	55A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	20A
220, monofásico	5	RBPED50M-20	23	55A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	30A
220, monofásico	7,5	RBPED75M-20	34	55A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	50A

220, monofásico	10	RBPED100M-20	45	55A	24 x 24 x 10 (609 x 609 x 254)	85 (39)	60A
220, monofásico	15	RBPED150M-20	68	95A	24 x 24 x 10 (609 x 609 x 254)	100 (45)	90A
220, monofásico	20	RBPED200M-20	91	95A	28 x 24 x 15.5 (711 x 609 x 394)	100 (45)	125A
220, monofásico	30	RBPED300M-20	136	175A	28 x 24 x 15.5 (711 x 609 x 394)	150 (68)	175A
220, monofásico	40	RBPED400M-20	182	280A	24 x 24 x 13 (609 x 609 x 330)	150 (68)	225A
220, monofásico	50	RBPED500M-20	227	280A	34 x 32 x 17 (863 x 812 x 431)	175 (79)	300A
220, monofásico	60	RBPED600M-20	273	280A	34 x 32 x 17 (863 x 812 x 431)	175 (79)	Consulte a fábrica
220, monofásico	75	RBPED750M-20	341	384A	34 x 32 x 17 (863 x 812 x 431)	175 (79)	Consulte a fábrica
220, monofásico	100	RBPED1000M-20	455	576A	34 x 32 x 17 (863 x 812 x 431)	175 (79)	Consulte a fábrica

ESPECIFICAÇÕES GERAIS 2R2

VOLTAGEM	KVA NOMINAL A UPS	MODELO	CORRENTE NOMINAL	CONMUTADOR NOMINAL*	DIM. RECINTO AL X AN X PRO PULG. (MM)	PESO LBS (KG)	INTERRUPTOR .NOM. OPCION**
208/120, trifásico	10	3RBPED100T-20	28	55A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	40A
208/120, trifásico	15	3RBPED150T-20	42	55A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	60A
208/120, trifásico	20	3RBPED200T-20	56	95A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	70A
208/120, trifásico	30	3RBPED300T-20	83	95A	24 x 24 x 13 (609 x 609 x 330)	125 (57)	125A
208/120, trifásico	40	3RBPED400T-20	111	175A	24 x 24 x 14 (609 x 609 x 356)	125 (57)	150A
208/120, trifásico	50	3RBPED500T-20	139	175A	24 x 24 x 14 (609 x 609 x 356)	125 (57)	175A
208/120, trifásico	60	3RBPED600T-20	167	175A	28 x 24 x 15.5 (711 x 609 x 393)	165 (75)	225A
208/120, trifásico	75	3RBPED700T-20	208	240A	34 x 32 x 17 (864 x 813 x 432)	165 (75)	250A
208/120, trifásico	100	3RBPED100T-20	278	384A	34 x 32 x 20 (864 x 813 x 508)	165 (75)	350A
380/220, trifásico	10	3RBPED100T-38	15	55A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	20A
380/220, trifásico	15	3RBPED150T-38	23	55A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	30A
380/220, trifásico	20	3RBPED200T-38	30	55A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	40A
380/220, trifásico	30	3RBPED300T-38	46	55A	24 x 24 x 13 (609 x 609 x 330)	125 (57)	60A
380/220, trifásico	40	3RBPED400T-38	61	95A	24 x 24 x 13 (609 x 609 x 330)	125 (57)	80A
380/220, trifásico	50	3RBPED500T-38	76	95A	24 x 24 x 13 (609 x 609 x 330)	125 (57)	100A
380/220, trifásico	60	3RBPED600T-38	91	95A	24 x 24 x 13	165	125A

					(609 x 609 x 330)	(75)	
380/220, trifásico	75	3RBPED700T-38	114	175A	24 x 24 x 14 (609 x 609 x 356)	165 (75)	150A
380/220, trifásico	100	3RBPED100T-38	152	175A	28 x 24 x 15.5 (711 x 609 x 393)	165 (75)	200A
480/277, trifásico	10	3RBPED100T-48	12	55A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	20A
480/277, trifásico	15	3RBPED150T-48	18	55A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	25A
480/277, trifásico	20	3RBPED200T-48	24	55A	24 x 24 x 13 (609 x 609 x 330)	100 (45)	40A
480/277, trifásico	30	3RBPED300T-48	36	55A	24 x 24 x 13 (609 x 609 x 330)	125 (57)	50A
480/277, trifásico	40	3RBPED400T-48	48	55A	24 x 24 x 13 (609 x 609 x 330)	125 (57)	70A
480/277, trifásico	50	3RBPED500T-48	60	95A	24 x 24 x 13 (609 x 609 x 330)	125 (57)	80A
480/277, trifásico	60	3RBPED600T-48	72	95A	24 x 24 x 13 (609 x 609 x 330)	165 (75)	100A
480/277, trifásico	75	3RBPED700T-48	90	95A	24 x 24 x 13 (609 x 609 x 330)	165 (75)	125A
480/277, trifásico	100	3RBPED100T-48	12	175A	28 x 24 x 15.5 (711 x 609 x 393)	165 (75)	175A